Material Safety Data Sheet

1. Product	and company identification
Product name :	PROPYLENE GLYCOL - USP MSDS # 00033938
Product use :	Solvent.
	ChemWorld.com 3939 Royal Drive, Ste 224 and 226, Kennesaw, GA 30144
Validation date : 2	2/10/2010.
In case of emergency	
	Spills Leaks Fire or Exposure Call Chemtrec: (800) 424-9300
2. Hazards	In Mexico: 01 800 00 214 00 In Columbia: 01 800 91 6012
	In Mexico: 01 800 00 214 00 In Columbia: 01 800 91 6012 identification
2. Hazards Physical state Odor	In Mexico: 01 800 00 214 00 In Columbia: 01 800 91 6012
Physical state	In Mexico: 01 800 00 214 00 In Columbia: 01 800 91 6012 identification : Liquid.
Physical state Odor	In Mexico: 01 800 00 214 00 In Columbia: 01 800 91 6012 identification : Liquid. : Characteristic. : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and available for employees and other users of this product.
Physical state Odor OSHA/HCS status	In Mexico: 01 800 00 214 00 In Columbia: 01 800 91 6012 identification : Liquid. : Characteristic. : While this material is not considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200), this MSDS contains valuable information critical to the safe handling and proper use of the product. This MSDS should be retained and availab for employees and other users of this product. / : FOR EXCIPIENT USE ONLY. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAG THIS PRODUCT IS NOT TO BE USED TO PRODUCE FOGS OR MISTS IN

3. Composition/information on ingredients

<u>Name</u>
Propylene glycol

CAS number%57-55-660 - 100

4. First aid measures

Eye contact	Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any contact lenses. Continue to rinse for at least 10 minutes. Get medical attention if irritation occurs.
Skin contact	Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Clean shoes thoroughly before reuse.
Inhalation	Move exposed person to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Get medical attention if symptoms occur. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
Ingestion	Wash out mouth with water. Move exposed person to fresh air. Aspiration hazard if swallowed. Can enter lungs and cause damage. Do not induce vomiting. Get medical attention. Never give anything by mouth to an unconscious person.
Notes to physician	: Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

5. Fire-fighting measures

Flash point Flammable limits	: Closed cup: 99°C (210.2°F) : Lower: 2.6% Upper: 12.6%
Products of combustion	: Decomposition products may include the following materials: carbon oxides
Extinguishing media	
Suitable	: Use an extinguishing agent suitable for the surrounding fire.
Not suitable	: None known.
Special exposure hazards	: In a fire or if heated, a pressure increase will occur and the container may burst.
	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	: Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

6. Accidental release measures

Personal precautions	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Put on appropriate personal protective equipment (see section 8).
Environmental precautions	:	Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods for cleaning up	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Dispose of via a licensed waste disposal contractor. Note: see section 1 for emergency contact information and section 13 for waste disposal.

7. Handling and storage

Handling	: Put on appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not ingest. Avoid contact with eyes, skin and clothing. Avoid breathing vapor or mist. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Empty containers retain product residue and can be hazardous. Do not reuse container.
Storage	: Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

8. Exposure controls/personal protection

Consult local authorities for acceptable exposure limits.

Preventive Measures	 Conditions of use, adequacy of engineering or other control measures, and actual exposures will dictate the need for specific protective devices at your workplace.
Engineering controls	: Use local exhaust ventilation to maintain airborne concentrations below the TLV. Suitable respiratory equipment should be used in cases of insufficient ventilation or where operational procedures demand it. For guidance on engineering control measures refer to publications such as the ACGIH current edition of 'Industrial Ventilation, a manual of Recommended Practice.'
Personal protection	
Eyes	 Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.
Skin	: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory	: Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.
Hands	 Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.

9. Physical and chemical properties

General information	
Appearance	
Physical state	: Liquid.
Color	: Colorless.
Odor	: Characteristic.
Odor threshold	: Not available.
Important health, safety	and environmental information
рН	: 6
Boiling point	: 186 to 189°C (366.8 to 372.2°F)
Melting point	: -59°C (-74.2°F)
Flash point	: Closed cup: 99°C (210.2°F)
2/10/2010	

9. Physical and chemical properties

Oxidizing properties Vapor pressure	: Not available. : 0.011 kPa (0.08 mm Hg)
Relative density	: 1.04
Octanol/water partition coefficient	: -1
Viscosity	: Kinematic: <0.2 cm ² /s (<20 cSt at 40°C)
Vapor density	: 2.6 [Air = 1]
Auto-ignition temperature	: 421°C (789.8°F)
VOC content	: 28% by ASTM D2369 (110°C, 60 minutes)

10. Stability and reactivity

Stability and reactivity	: The product is stable.	
Hazardous polymerization	: Under normal conditions of storage and use, hazardous polymerization will not occur.	
Hazardous decomposition products	: Decomposition products may include the following materials: carbon oxides	

11. Toxicological information

Toxicity data

Product/ingredient name	Test	Species	Result	Exposure
Propylene glycol	LD50 Oral	Rat	22000 to 31000 mg/kg	- '
	LD50 Dermal	Rabbit	21000 mg/kg	-

Potential acute health effects

Ingestion Inhalation	Aspiration hazard if swallowed. Can enter lungs and cause damage. No known significant effects or critical hazards.		
Eyes	No known significant effects or critical hazards.		
Skin	No known significant effects or critical hazards.		
Potential chronic health effects			
Target organs	: None known.		
Carcinogenicity	: No known significant effects or critical hazards.		
Mutagenicity Teratogenicity	No known significant effects or critical hazards.No known significant effects or critical hazards.		
Fertility effects	: No known significant effects or critical hazards.		
Developmental effects	: No known significant effects or critical hazards.		

12. Ecological information

Bioaccumulative potential			
Product/ingredient name	<mark>LogP₀w</mark>	BCF	Potential
Propylene glycol	-1		low

Environmental effects : This product shows a low bioaccumulation potential.

13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

14. Transport information

Transportation Emergency Number 1-800-424-9300 (CHEMTREC).

Regulatory information	UN number	Proper shipping name	Class	PG*	Label	Additional information
DOT Classification	Not regulated.					-
TDG Classification	Not regulated.					-
IMDG Class	Not regulated.		-	-		-
IATA-DGR Class	Not regulated.		-	-		-

PG* : Packing group

15. Regulatory information

United States HCS Classification U.S. Federal regulations	 Not regulated. United States inventory (TSCA 8b): All components are listed or exempted. 			
CERCLA: Hazardous substances. : No ingredients listed.				
SARA 313	: No ingredients listed.			
	This product does not contain nor is it manufactured with ozone depleting substances.			
California Prop 65	 This product contains no listed substances known to the State of California to cause cancer, birth defects or other reproductive harm, at levels which would require a warning under the statute. 			
<u>Canada</u>				
WHMIS (Canada)	: Not controlled under WHMIS (Canada).			
CEPA (DSL)	: All components are listed or exempted.			

This product has been classified in accordance with the hazard criteria of the CPR (Controlled Products Regulations) and this MSDS (Material Safety Data Sheet) contains all the information required by the CPR.

16. Other information Label requirements : FOR EXCIPIENT USE ONLY. ASPIRATION HAZARD IF SWALLOWED - CAN ENTER LUNGS AND CAUSE DAMAGE. THIS PRODUCT IS NOT TO BE USED TO PRODUCE FOGS OR MISTS IN THEATRICAL, MUSICAL, OR OTHER ENTERTAINMENT PERFORMANCES. Hazardous Material 0 ż Health Information System (U.S.A.) 1 Fire hazard 0 Reactivity **National Fire Protection** Flammability Association (U.S.A.) Instability Health Date of printing : 2/10/2010. : 10 February 2010 Date of issue Date of previous issue 8/5/2008

Notice to reader

While the information and recommendations in this publication are to the best of our knowledge, information and belief accurate at the date of publication, NOTHING HEREIN IS TO BE CONSTRUED AS A WARRANTY, EXPRESS OR OTHERWISE.

IN ALL CASES, IT IS THE RESPONSIBILITY OF THE USER TO DETERMINE THE APPLICABILITY OF SUCH INFORMATION AND RECOMMENDATIONS AND THE SUITABILITY OF ANY PRODUCT FOR ITS OWN PARTICULAR PURPOSE.

THE PRODUCT MAY PRESENT HAZARDS AND SHOULD BE USED WITH CAUTION. WHILE CERTAIN HAZARDS ARE DESCRIBED IN THIS PUBLICATION, NO GUARANTEE IS MADE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.

Hazards, toxicity and behaviour of the products may differ when used with other materials and are dependent upon the manufacturing circumstances or other processes. Such hazards, toxicity and behaviour should be determined by the user and made known to handlers, processors and end users.

NO PERSON OR ORGANIZATION EXCEPT A DULY AUTHORIZED HUNTSMAN EMPLOYEE IS AUTHORIZED TO PROVIDE OR MAKE AVAILABLE DATA SHEETS FOR HUNTSMAN PRODUCTS. DATA SHEETS FROM UNAUTHORIZED SOURCES MAY CONTAIN INFORMATION THAT IS NO LONGER CURRENT OR ACCURATE. NO PART OF THIS DATA SHEET MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM, OR BY ANY MEANS, WITHOUT PERMISSION IN WRITING FROM HUNTSMAN. ALL REQUESTS FOR PERMISSION TO REPRODUCE MATERIAL FROM THIS DATA SHEET SHOULD BE DIRECTED TO CHEMWORLD.COM, PRODUCT SAFETY AT THE ABOVE ADDRESS.

Indicates information that has changed from previously issued version.